



Performance Data Sheet

QT5-1 & QT15-1						
Model	Rated Flow-rate (gpm)	Rated Flow-rate (lpm)	Rated Capacity (gallons)	Rated Capacity (liters)	Replacement component model number	Replacement component Part #
QT5-1	0.75	2.85	6,000	22,712	CTO-Q5	300-05803
QT15-1	0.75	2.85	6,000	22,712	CTOS-Q5	300-05804

Maximum Working Pressure: 125 Psi / 8.6 Bar

Maximum Operating Temperature: 100°F/38°C

It is recommended that filters be changed every six months, when capacity is reached or when flow becomes inadequate.

This system has been tested according to NSF/ANSI 42 for reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI 42.

CHLORINE REDUCTION		
SUBSTANCE	INFLUENT CHALLENGE CONCENTRATION	MAXIMUM PERMISSIBLE PRODUCT WATER CONCENTRATION/PERCENT REDUCTION REQUIREMENT
CHLORINE	2.0 mg/L \pm 10%	\geq 50%

While Testing was performed under the standard laboratory conditions, actual performance may vary due to local water conditions.

QT5-1 & QT15-1, are certified by IAPMO R & T to NSF/ANSI Standard 42 for the reduction of Chlorine, Taste & Odor.

Do not use on water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

This product is for commercial use only and must be installed and maintained according to manufacturer's guidelines.

See the installation, operation and maintenance manual for installation instructions.

See Warranty information in operation and maintenance manual. For complete warranty information, contact OptiPure customer service or go to www.optipurewater.com.

